

# Win Dialog Plus



400-800 VA  
Single-phase

## Highlights

- Automatic Voltage Regulator (AVR)
- Advanced communication
- Automatic battery test



The WIN DIALOG PLUS series includes the 400-600-800VA models and uses digital technology. The load is powered from the mains through an AVR to stabilise brownouts, sags, and surge voltages, and EMI filters to suppress spikes and transients.

When the mains fails, the load is powered from a pseudo-sinewave inverter, to provide sufficient runtime for computer system shutdown using PowerShield<sup>3</sup>. PowerShield<sup>3</sup>, software, is downloadable free of charge from [www.riello-ups.com](http://www.riello-ups.com).

### Features

- Stabilisation and filtering of the mains power supply using a built-in AVR and EMI filters for the elimination of atmospheric disturbances
- Cold Start capability: the UPS can power up without a mains supply present
- High reliability with built-in battery test
- Auto restart (when mains power is restored, after discharge of the batteries)
- Supplied with two IEC cables for powering the loads

MODELS	WPG 400	WPG 600	WPG 800
POWER	400VA/240W	600VA/360W	800VA/480W
INPUT			
Nominal voltage	220-230-240 Vac		
Input voltage tolerance	230 Vac ( $\pm 25\%$ )		
Frequency	50 or 60 Hz with automatic selection		
OUTPUT			
Voltage during mains operation	230 Vac (-8%, +10%)		
Voltage during battery operation	230 Vac (+/- 5%)		
Frequency during battery operation	50 or 60 Hz (+/- 0.5%)		
Battery waveform	Pseudo sine wave		
BATTERIES			
Type	VRLA AGM lead acid maintenance-free		
Charging time	6-8 h		
OTHER FEATURES			
Net weight (kg)	5.8		6.2
Gross weight (kg)	6.9		7.3
Dimensions (hwd) (mm)	152 x 110 x 325		
Packaging dimensions (hwd) (mm)	140 x 380 x 230		
Communication	USB		
Output socket	3 IEC SOCKET 320 C13		
Regulations	EN 62040-1-1 and Directive EN 62040-3 EN 62040-2 and Directive 2004/108 EC		
Trademarks	CE		
Ambient temperature	0°C / +40°C		
Colour	Dark grey RAL 7016		
Altitude and relative humidity	6000 m max altitude, <95% non-condensing		
Standard equipment provided	2 output supply cables, communications software; user manual		

## details

### Advanced communication

- Advanced communication, multi-platform, for all operating systems and network environments: PowerShield<sup>3</sup> supervision and shutdown software for Windows operating systems 7, 2008, Vista, 2003, XP, Linux, Mac OS X and Sun Solaris
- Standard USB interface

### 2-YEAR WARRANTY

